


UPV-S

Three Phase Solar+Storage Hybrid Inverters



• Features

- High stability, modular design support N+1.
- Bi-directional Power Conversion System.
- Built-in transformer.
- Support self-generation, micro-grid application.
- Supports on/off grid.
- Photovoltaic can be connected to a maximum of twice the capacity of the device.
- Dual-stage topology, wide battery voltage input range.
- With MPPT function to enhance system power generation.
- Self-contained solar storage operation strategy.
- Support communication with BMS, EMS system.

• Applications



Self-Consumption



Off grid



Demand Charge



Back Up



DG+BESS



Micro-grid



Smooth output



Peak Shifting

• Technical Parameter

UPV-S Series Solar+Storage Hybrid Inverters										
Model	0.4-50KW	0.4-100KW	0.4-150KW	0.4-200KW	0.4-250KW	0.5-50KW	0.5-100KW	0.5-150KW	0.5-200KW	0.5-250KW
Stand-alone Mode										
AC output voltage	400V±10%(Controllable)					480V±10%(Controllable)				
AC output current	72A (Max 79A)	144A (Max 159A)	216A (Max 238A)	288A (Max 317A)	360A (Max 396A)	60A(Max 66A)	120A(Max 132A)	180A (Max 196A)	240A (Max 264A)	300A (Max 330A)
Nominal AC output power	50kW	100kW	150kW	200kW	250kW	50kW	100kW	150kW	200kW	250kW
AC Max Power	55kW	110kW	165kW	220kW	275kW	55kW	110kW	165kW	220kW	275kW
Output THDu	≤3%(Linear load)									
AC frequency	50/60Hz					60Hz				
AP PF	0.99/-1~1									
Overload Capability	120% 1min									
Battery voltage range	400~600V (Rated 512V)		600 ~ 900V			400~600V (Rated 512V)		600 ~ 900V		
Battery DC Max Current	120A	240A	275A	367A	458A	120A	240A	275A	367A	458A
PV Voltage Range	520~900V (MPPT 520V~800V)		300~800V			520~900V (MPPT 520V~800V)		300~800V		
PV DC Max Current	192A	384A	360A	480A	600A	192A	384A	360A	480A	600A
Utility grid-interactive Mode										
AC voltage range	400V±15%					480V±15%				
AC rated current	72A	144A	216A	288A	360A	60A	120A	180A	240A	300A
Nominal AC output power	50kW	100kW	150kW	200kW	250kW	50kW	100kW	150kW	200kW	250kW
AC frequency	50Hz / 60Hz±2.5Hz					60Hz±0.2%±2.5Hz				
Output THDI	≤3%									
AP PF	0.99/-1~1									
Battery voltage range	400~600V (Rated 512V)		600 ~ 900V			400~600V (Rated 512V)		600 ~ 900V		
Batter DC Max Current	120A	240A	275A	367A	458A	120A	240A	275A	367A	458A
PV Voltage Range	520~900V (MPPT 520V~800V)		300~800V			520~900V (MPPT 520V~800V)		300~800V		
PV DC. Max Current	192A	384A	360A	480A	600A	192A	384A	360A	480A	600A
Other										
Peak efficiency	≥96%		≥95.5%			≥96%		≥95.5%		
Protection	Overtemperature protection, AC over/under voltage protection, Over/under frequency protection, Emergency power off, AC phase reverse, Fan/relay failure, Over/under load protection, Ground faultcircuit Interrupter, Anti-islanding									
Configurable protection limits	Upper/Lower AC Voltage/Frequency limit, Battery end of discharge voltage.									
AC connection	3P4W									
Display	7"color touch screen									
Communication	RS485,CAN,Ethernet									
Isolation	Built-in Transformer									
Physical										
Cooling	Forced air cooling									
Noise	≤70dB									
Enclosure	IP20/IP54									
Max elevation	3000m/10000 feet (>2000m/6500 feet derating)									
Operating temp	-20°C~ 50°C (>45°C derating)									
Humidity	0~95% (No condensing)									
Size (W*H*D)	800*2200*1050mm		1350*2200*1050mm			800*2200*1050mm		1350*2200*1050mm		
Weight	/	/	1300kg	1650kg	2000kg	/	/	1300kg	1650kg	2000kg